		<div>NATIONAL INSTITUTE OF OCEAN TECHNOLOGY</div> <div>GEOTECHNICAL DIVISION</div> <div>CHENNAI</div>																					
Project: SETHU SAMUDRA CHANNEL PROJECT																							
VIBRO CORE SAMPLES											SUMMARY OF LABORATORY TEST RESULTS												
Vibro Core No	Latitude	Longitude	Water depth (m)	Depth (m)	Description	N M C (%)	Specific Gravity G <sub>s</sub>	w (g/cc)	γ <sub>e</sub> (g/cc)	Void Ratio (e)	Degree of Saturation (S <sub>v</sub> )	Atterberg Limits			Grain Size Analysis						Torvane (ps)	Chemical Analysis	
												LL (%)	PL (%)	PI (%)	Shells (%)	Gravel (%)	Coarse Sand (%)	Medium Sand (%)	Fine Sand (%)	Silt & Clay (%)		Ca CO <sub>3</sub> (%)	Organic Matter (%)
AB-1	09 11 07.05	79 29 13.04	7.0	0.20	Greyish silty medium to fine SAND with broken shells	17	2.67	2.03	1.74	0.53	84.82				4	0	0	29	53	14			
				0.37	Top medium, loose sand, at bottom sand with shell pieces and few pieces of hard rock and coral. Top a thin veneer of loose clayey material.	18		1.84	1.56						10	0	0	49	39	2			
AB-2	09 12 15.15	79 29 13.05	8.9	0.05	Greyish silty medium to fine SAND with broken shells	21		1.99	1.64						7	0	0	27	58	10			
				0.10	- DO -	20		1.95	1.63														
				0.90	Greyish medium to fine SAND with shells	20	2.64	1.83	1.53	0.73	72.77				4	0	0	40	51	5			
				1.80	Top loose sand, bottom semi dense olive grey to grey sand with minor pieces of clayey calcareous sand stones	24	2.64	1.88	1.50	0.78	83.36				5	6	1	29	45	14			



Project: SETHU SAMUDRA CHANNEL PROJECT																							
VIBRO CORE SAMPLES										SUMMARY OF LABORATORY TEST RESULTS													
Vibro Core No	Latitude	Longitude	Water depth (m)	Depth (m)	Description	NMC (%)	Specific Gravity G <sub>s</sub>	T <sub>200</sub> (g/cc)	T <sub>425</sub> (g/cc)	Void Ratio (e)	Degree of Saturation (S <sub>v</sub> )	Atterberg Limits			Grain Size Analysis						Torsione (kPa)	Chemical Analysis	
												LL (%)	PL (%)	PI (%)	Shel% (%)	Gravel (%)	Coarse Sand (%)	Medium Sand (%)	Fine Sand (%)	Silt & Clay (%)		Ca CO <sub>3</sub> (%)	Organic Matter (%)
AB-3	09 14 8.615	79 29 8.312	9.15	0.0	Greyish silty medium to fine SAND	23	2.65	1.67	1.40	0.29	97.99				3	5	1	25	52	14			
				0.50	Top loose olive grey silty sand, hard and clayey calcareous sand stone at bottom in gravel size										0	29	2	19	32	18			
AB-4	09 11 01.27	79 28 57.13	6.5	0.0	Light greyish medium to fine SAND with shells	20		1.68	1.55						5	0	0	30	58	7			
				0.60	Brownish silty medium to fine SAND	15		1.73	1.50														
				1.25	Top thin veneer of silty clay followed by sandy material, bottom sand with shell pieces partially dense	17	2.68	1.79	1.52	0.78	98.89				3	0	1	37	57	2			
BC-1	09 17 11.65	79 28 33.04	8.4		NO Sample																		
BC-2	09 20 13.6	79 27 47.83	11.9	0.0	Greyish very soft silty CLAY							85	26	59							5.2	1.75	
				1.40	Greyish soft clayey silty fine SAND with shells	50	2.71	1.72	1.15	1.38	98.85				7	0	0	10	41	42			
				2.63	Loose olive grey silty clay at top and dark grey firm clay at bottom	28		1.60	1.25			67	34	33							2.3	1.99	

Project: SETHU SAMUDRA CHANNEL PROJECT																								
VIBRO CORE SAMPLES											SUMMARY OF LABORATORY TEST RESULTS													
Vibro Core No	Latitude	Longitude	Water depth (m)	Depth (m)	Description	N/M C (%)	Specific Gravity G <sub>s</sub>	γ <sub>s</sub> (g/cc)	γ <sub>d</sub> (g/cc)	Void Ratio (e)	Degree of Saturation (S <sub>v</sub> )	Atterberg Limits			Grain Size Analysis						Torsane (kpa)	Chemical Analysis		
												LL (%)	PL (%)	PI (%)	Shells (%)	Gravel (%)	Coarse Sand (%)	Medium Sand (%)	Fine Sand (%)	Silt & Clay (%)		Ca CO <sub>3</sub> (%)	Organic Matter (%)	
BC-3	09 15 12.34	79 28 59.06	9.5	0.0	Dark greyish silty fine SAND with shells	31		1.65	1.49							5	3	4	13	53	13			
				0.42	Olive grey medium to fine sand at top with pieces of white sand stone with sand at bottom										0	43	6	17	22	12				
BC-4	09 17 03.50	79 28 29.22	8	0.0	Greyish medium to fine SAND	33	2.65	1.90	1.42	0.69	89.67					3	0	2	39	43	13			
				0.60	Top medium to fine sand with shell pieces. Medium to fine sand at bottom	23	2.72	1.93	1.58	0.72	88.70				3	0	5	34	47	11				
BC-5	09 20 35.32	79 27 38.83	12.12	0.0	Greyish calcareous silty SAND	77	2.65	1.51	0.55	2.13	96.15					15	0	0	3	30	49		6.3	0.87
				1.0	Greyish calcareous clayey silty SAND	43		1.66	1.16							15	0	0	2	36	44			
				2.60	Grey calcareous silty sand	39		1.73	1.28			61	37	24									75	



Project: SETHU SAMUDRA CHANNEL PROJECT																									
VIBRO CORE SAMPLES										SUMMARY OF LABORATORY TEST RESULTS															
Vibro Core No	Latitude	Longitude	Water depth (m)	Depth (m)	Description	N.M.C. (%)	Specific Gravity G <sub>s</sub>	w <sub>L</sub> (g/cc)	w <sub>n</sub> (g/cc)	Void Ratio (e)	Degree of Saturation (S <sub>v</sub> )	Atterberg Limits			Grain Size Analysis						Torsion (kpa)	Chemical Analysis			
												LL (%)	PL (%)	PI (%)	Ca CO <sub>3</sub> (%)	Organic Matter (%)	Coarse Sand (%)	Medium Sand (%)	Fine Sand (%)	Silt & Clay (%)		Ca CO <sub>3</sub> (%)	Organic Matter (%)		
BC-8	09 18 20.15	79 28 23.58	10.4	0.0	Greyish silty fine SAND with shells	42		1.68	1.12						5	0	3	17	52	23					
				0.60	In top shell clayey sand to silty sand at bottom calcareous clayey sand stone the sand stone pieces are hard. Since the presence of hard formations are observed the coring was repeated at 18.05 hours were similar results are seen	18									0	28	21	13	19	19					
CD-1	09 28 06.60	79 25 48.05	12.75	0.00	Greyish very soft silty CLAY	180						132	61	77											
				0.40	-DO-	160																1			
				0.60	Dark Greyish very soft CLAY	151		1.28	0.50																
				1.30	-DO-	154	2.53	1.20	0.51	3.66	98.35	120	65	54								5			
				2.00	Top soft olive grey silty clay Bottom at 2.10m compact stiff dark grey blackish clay at 2.0m 5m clay	35																55	5.5	0.62	



Project: SETHU SAMUDRA CHANNEL PROJECT																							
VIBRO CORE SAMPLES										SUMMARY OF LABORATORY TEST RESULTS													
Vibro Core No	Latitude	Longitude	Water depth (m)	Depth (m)	Description	N.M.C (%)	Specific Gravity G <sub>s</sub>	γ <sub>w</sub> (g/cc)	γ <sub>s</sub> (g/cc)	Void Ratio (e)	Degree of Saturation (S <sub>r</sub> )	Atterberg Limits			Grain Size Analysis						Tonnage (kgs)	Chemical Analysis	
												LL (%)	PL (%)	FI (%)	Shells (%)	Gravel (%)	Coarse Sand (%)	Medium Sand (%)	Fine Sand (%)	Silt & Clay (%)		Ca CO <sub>3</sub> (%)	Organic Matter (%)
CD-2	09 30 10.01	79 24 07.85	13.38	0.0	Greyish very soft silty CLAY	147	2.59	1.26	0.51	2.08	93.95	125	81	64									
				0.80	Greyish soft silty CLAY	79		1.51	0.84			70	27	43							4		
				1.75	Top loose silty clay with lumps of semi compact clay and piece of small sand stone like material. Bottom olive grey stiff clay	35	2.68	1.85	1.34	1.02	100	62	35	27							112		
CD-3	09 34 49.70	79 22 21.45	13.2	0.10	Greyish very soft silty CLAY	127		1.38	0.60			112	45	67							1	6.5	1.17
				1.0	Greyish very soft CLAY	75	2.63	1.48	0.84	2.13	92.58										7		
				1.85	Top olive grey soft silty clay with shell pieces. Bottom dark green to black compact stiff clay.	50		1.75	1.17			80	35	42							45		
CD-4	09 39 03.82	79 20 47.32	13	0.20	Olive greenish grey very soft silty CLAY	162		1.30	0.49			132	36	60							1		
				1.05	Top semi consolidated olive grey soft clay with shell, bottom dark olive grey firm to stiff clay	42		1.88	1.32												70		

Project: SETHU SAMUDRA CHANNEL PROJECT																								
VIBRO CORE SAMPLES										SUMMARY OF LABORATORY TEST RESULTS														
Vibro Core No	Latitude	Longitude	Water depth (m)	Depth (m)	Description	N.M.C (%)	Specific Gravity $G_s$	$w_L$ (g/cc)	$w_p$ (g/cc)	Void Ratio (e)	Degree of Saturation ( $S_v$ )	Atterberg Limits			Grain Size Analysis						Towara (kg/t)	Chemical Analysis		
												LL (%)	PL (%)	PI (%)	Shells (%)	Gravel (%)	Coarse Sand (%)	Medium Sand (%)	Fine Sand (%)	Silt & Clay (%)		Ca CO <sub>3</sub> (%)	Organic Matter (%)	
CD-5	09 23 04.25	79 27 08.75	12.7	0.0	Greyish very soft silty CLAY	235		1.13	0.34													1	1.1	12.44
				1.35	Greyish very soft CLAY.	72		1.59	0.62			55	30	25								4		
				2.30	Top olive grey soft silty clay, at 1.35m olive grey semi consolidated sandy clay, at bottom olive grey compact and consolidated firm clay	34	2.66	1.27	1.40	0.90	97.53	60	38	24							70			
CD-6	09 35 20.58	79 22 17.12	13.2	0.1	Olive greenish grey very soft CLAY	102		1.45	0.71			60	30	50								1		
				0.90	Olive green sandy CLAY with shells	51	2.85	1.71	1.13	1.35	100				12	0	0	2	20	60	3			
				1.40	Top loose olive grey soft clay at 0.33m semi consolidated sandy clay, bottom dark grey firm clay with shell pieces	41	2.63	1.79	1.26	1.09	99.17	60	37	23							40			
CD-7	09 26 28.54	79 25 31.83	13.0	0.0	Olive green Very soft CLAY	155		1.30	0.51			143	33	110										
				1.0	Greyish sandy clayey SILT with broken shells	57		1.81	1.03						2	0	5	6	4	83	4			
				2.0	Top olive grey soft clay, at bottom firm dark grey to blackish clay	40		1.73	1.23			50	24	26							55			

Project: SETHU SAMUDRA CHANNEL PROJECT																							
VIBRO CORE SAMPLES											SUMMARY OF LABORATORY TEST RESULTS												
Vibro Core No	Latitude	Longitude	Water depth (m)	Depth (m)	Description	N.M.C (%)	Specific Gravity G <sub>s</sub>	γ <sub>e</sub> (g/cc)	γ <sub>d</sub> (g/cc)	Void Ratio (e)	Degree of Saturation (S <sub>v</sub> )	Atterberg Limits			Grain Size Analysis						Tensile (kPa)	Chemical Analysis	
												LL (%)	PL (%)	PI (%)	Shells (%)	Gravel (%)	Coarse Sand (%)	Medium Sand (%)	Fine Sand (%)	Silt & Clay (%)		Ca CO <sub>3</sub> (%)	Organic Matter (%)
CD-5	09 34 48.15	79 22 12.25	13.3	0.10	Olive green very soft sandy silty CLAY	78	2.65	1.51	0.64	2.18	95.43	85	26	59							1	5.1	2.00
				1.0	Greyish very soft silty CLAY	55		1.52	0.62			75	22	46							5		
				2.0	Top loose olive grey sandy silty clay, at bottom dark olive grey firm clay	43		1.78	1.12			90	41	49							55		
DE-1	09 57 01.51	79 32 23.49	12.7	0.0	Greenish grey very soft CLAY	154		1.24	0.49			132	36	96							1		
				1.50	Greenish grey firm CLAY	121		1.37	0.62			112	32	80							55		
				2.30	Greyish clayey sandy SILT with broken shells	62		1.65	1.01			72	29	43	16	0	0	15	27	42	6		
				3.0	Top olive grey loose soft clay. Bottom olive grey stiff clay	27		1.68	1.56			50	24	26							75		

Project: SETHU SAMUDRA CHANNEL PROJECT																							
VIBRO CORE SAMPLES										SUMMARY OF LABORATORY TEST RESULTS													
Vibro Core No	Latitude	Longitude	Water depth (m)	Depth (m)	Description	N M.C (%)	Specific Gravity G <sub>s</sub>	w <sub>L</sub> (g/cc)	w <sub>n</sub> (g/cc)	Vod Ratio (e)	Degree of Saturation (S <sub>v</sub> )	Atterberg Limits			Grain Size Analysis						Torsion (kpa)	Chemical Analysis	
												LL (%)	PL (%)	PI (%)	Shells (%)	Gravel (%)	Coarse Sand (%)	Medium Sand (%)	Fine Sand (%)	Silt & Clay (%)		Ca CO <sub>3</sub> (%)	Organic Matter (%)
DE-2	09°53'04.72	79°29'27.95	13.31	0.0	Greenish grey very soft Clay	152		1.30	0.52			129	36	93							2.8	1.51	
				1.0	Greyish soft CLAY	123		1.38	0.62												5		
				1.65	Top olive grey loose soft clay, at bottom light biscuit brown compact stiff clay. Just above this there is somewhat plastic stiff compact white to pale clay with small rock pieces	43	2.62	1.76	1.23	1.13	99.89	87	36	51							50		
DE-3	09°44'04.58	79°22'48.82	12.5	0.10	Olive green very soft silty CLAY	57		2.18	1.37			70	31	39							1		
				0.80	Grey sh very soft CLAY	62		1.52	0.63			77	36	41							4		
				1.85	Top loose olive grey to dark olive grey silty clay, bottom dark grey to grey firm clay	55	2.87	1.69	1.08	1.47	99.74	72	35	37							45		




Project: SETHU SAMUDRA CHANNEL PROJECT																							
VIBRO CORE SAMPLES										SUMMARY OF LABORATORY TEST RESULTS													
Vibro Core No	Latitude	Longitude	Water depth (m)	Depth (m)	Description	N M C (%)	Specific Gravity G <sub>s</sub>	w <sub>L</sub> (g/cc)	w <sub>U</sub> (g/cc)	Void Ratio (e)	Degree of Saturation (S <sub>r</sub> )	Atterberg Limits			Grain Size Analysis						Torsione (kPa)	Chemical Analysis	
												LL (%)	PL (%)	PI (%)	Shells (%)	Gravel (%)	Coarse Sand (%)	Medium Sand (%)	Fine Sand (%)	Silt & Clay (%)		Ca CO <sub>3</sub> (%)	Organic Matter (%)
DE-4	09 42 44.89	78 24 37.42	13.0	0.0	Greenish grey very soft CLAY	245		1.21	0.35			138	34	82							1	5.3	2.34
				0.60	Greenish grey very soft CLAY	102	2.45	1.41	0.70	2.50	88.88	87	23	65							6		
				1.60	Top olive grey loose, at bottom dark grey to black clay, firm	42		1.70	1.10												50	3.4	0.82
DE-5	09 42 51.27	78 21 42.17	13.5	0.0	Greyish very soft Clay	107						103	31	77									
				0.60	Greyish very soft: CLAY	97		1.48	0.74												6		
				1.35	Top olive grey soft clay, bottom dark grey to black firm clay	39	2.64	1.78	1.28	1.08	86.85	82	22	30							30		
DE-6	09 41 10.28	78 20 28.31	12.5	0.00	Greenish very soft CLAY	170		1.23	0.45			114	33	81							1		
				0.75	Bottom core recovered 0.75m. Top loose olive grey soft clay with minor shells, at bottom dark olive grey firm silty clay with minor pieces of shells	42		1.67	1.12												55		



Project: SETHU SAMUDRA CHANNEL PROJECT																											
VIBRO CORE SAMPLES										SUMMARY OF LABORATORY TEST RESULTS																	
Vibro Core No	Latitude	Longitude	Water depth (m)	Depth (m)	Description	N M C (%)	Specific Gravity G <sub>s</sub>	w (g/cc)	w <sub>d</sub> (g/cc)	Void Ratio (e)	Degree of Saturation (FS)	Atterberg Limits			Grain Size Analysis						Torvane (kpa)	Chemical Analysis					
												LL (%)	PL (%)	PI (%)	Shells (%)	Gravel (%)	Coarse Sand (%)	Medium Sand (%)	Fine Sand (%)	Silt & Clay (%)		Ca CO <sub>3</sub> (%)	Organic Matter (%)				
DE-7	08 49 01.28	78 26 08.57	13.12	0.00	Olive green very soft silty CLAY	210		1.22	0.39													1.7	3.02				
				1.35	Greyish very soft silty CLAY	117		1.35	0.62															112	34	76	5
				2.60	Top olive grey loose with minor crumbling shell pieces at 1.30m olive grey semi consolidated slightly plastic clay. Bottom olive grey sticky firm clay. This is not as stiff as earlier samples, it is more plastic	52		1.61	1.05																		
DE-8	08 49 08.60	78 23 40.20	12.9	0.0	Olive green very soft silty CLAY	235	2.55	1.18	0.35	2.81	99.05	122	36	86									1				
				0.90	Greenish grey very soft CLAY	102		1.40	0.87			85	38	47									4				
				1.65	Top olive grey loose silty clay bottom dark olive grey to olive brown sticky firm clay	46		1.74	1.16			72	40	32									20				

Project: SETHU SAMUDRA CHANNEL PROJECT																								
VIBRO CORE SAMPLES										SUMMARY OF LABORATORY TEST RESULTS														
Vibro Core No	Latitude	Longitude	Water depth (m)	Depth (m)	Description	N M C (%)	Specific Gravity G <sub>s</sub>	w (g/cc)	w <sub>L</sub> (g/cc)	Void Ratio (e)	Degree of Saturation (%)	Atterberg Limits			Grain Size Analysis						Tonvane (kpa)	Chemical Analysis		
												LL (%)	PL (%)	PI (%)	Shells (%)	Gravel (%)	Coarse Sand (%)	Medium Sand (%)	Fine Sand (%)	Silt & Clay (%)		Ca CO3 (%)	Organic Matter (%)	
DE-9	08 42 30.13	79 21 49.94	12.6	0.0	Greenish grey very soft CLAY	154	2.51	1.33	0.56	3.48	98.55	100	37	63							1			
				0.75	Greyish very soft CLAY	57	2.71	1.50	0.80	2.39	98.75											2		
				1.45	Top loose olive grey silty clay at 75 cm soft clay, bottom dark grey to black firm clay	51		1.69	1.12													60		
DE-10	08 44 21.29	79 23 20.80	13.39	0.00	Greenish grey very soft CLAY	185		1.20	0.40													7.2	1.50	
				0.60	Greyish very soft CLAY	109		1.41	0.67													5		
				1.60	Loose olive grey soft clay, bottom sticky dark grey to dark firm clay	52	2.73	1.70	1.12	1.44	98.75	47	23	24								50		
DE-11	08 51 59.40	79 29 03.55	12.6	0.00	Olive green very soft CLAY	185		1.19	0.40			77	28	49										
				1.02	Greyish very soft silty CLAY	113		1.39	0.65			108	39	67								3		
				2.0	Top loose olive grey soft clay, with some shells, at bottom olive grey somewhat plastic firm clay	50	2.7	1.72	1.14	1.37	98.85	111	45	65								65		

Project: SETHU SAMUDRA CHANNEL PROJECT																								
VIBRO CORE SAMPLES										SUMMARY OF LABORATORY TEST RESULTS														
Vibro Core No	Latitude	Longitude	Water depth (m)	Depth (m)	Description	N M.C (%)	Specific Gravity G <sub>s</sub>	w (g/sec)	T <sub>6</sub> (g/cc)	Void Ratio (e)	Degree of Saturation (S <sub>r</sub> )	Atterberg Limits			Grain Size Analysis						Tensile (kg/cm <sup>2</sup> )	Chemical Analysis		
												LL (%)	PL (%)	PI (%)	Shells (%)	Gravel (%)	Coarse Sand (%)	Medium Sand (%)	Fine Sand (%)	Silt & Clay (%)		Ca CO <sub>3</sub> (%)	Organic Matter (%)	
S.E.-1	10 05 25.03	80 02 58.14	10.5	0.20	Greyish soft silty fine sandy CLAY	38	2.69	1.25	1.26	0.88	88.02	37	22	15	4	0	0	6	37	51		4.0	0.25	
				1.15	Greyish soft silty CLAY	45		1.70	1.17			50	22	28										
				2.25	Top of five loose sandy clay pieces minor shells. At 2.25m light grey to cement colour sand clay the small pieces of sand stone. Core barrel bottom white to half white semi plastic sand to silty clay	17	2.62								0	20	10	15	16	36		6.8	0.08	
S.E.-2	10 05 55.08	79 55 37.51	7	0.28	Brownish medium to fine SAND	20		1.94	1.81						1	0	0	32	65	1				
				1.31	Top light brown medium to fine sand along with some fine black sand with pieces of shells. At bottom white to half white medium to fine sand. The sand appears loose and is probably at depth due to which not much penetration	18	2.69	1.88	1.59						1	0	0	15	76	8				



Project: SETHU SAMUDRA CHANNEL PROJECT																								
VIBRO CORE SAMPLES										SUMMARY OF LABORATORY TEST RESULTS														
Vibro Core No	Latitude	Longitude	Water depth (m)	Depth (m)	Description	N M C (%)	Specific Gravity G <sub>s</sub>	w (g/cc)	w <sub>a</sub> (g/cc)	Void Ratio (e)	Degree of Saturation (%)	Atterberg Limits			Grain Size Analysis						Torvane (kpa)	Chemical Analysis		
												LL (%)	PL (%)	PI (%)	Shells (%)	Gravel (%)	Coarse Sand (%)	Medium Sand (%)	Fine Sand (%)	Silt & Clay (%)		Ca CO <sub>3</sub> (%)	Organic Matter (%)	
E-E <sub>1</sub> -3a	10 01 45.20	78 43 22.59	12	0.20	Greyish very soft fine sandy CLAY with shells	54	2.69	1.52	0.98	1.74	23.24	65	12	38	10	0	0	4	17	70		4.4	1.17	
				1.37	Top grey soft sand clay. At bottom light colour plastic clay silty to silty clay with pieces of white calcareous sand stone. Since the top is initially 11.50m and there are presence of calcareous sand stone it was decided to take another vibro core here.	25		1.06	1.58						1	0	3	7	80	23				
E-E <sub>1</sub> -3b	10 01 45.68	78 43 21.05	12.1	0.20	Greyish very soft silty CLAY with broken shells	38		1.23	1.34			32	NP								6	3.2	0.34	
				1.47	Same as 3A. The calcareous sand stone is initially bit soft and clayey. This shows from around 11.00m it is lightly hard	23	2.65	2.01	1.04	0.62	96.86	30	NP											

Project: SETHU SAMUDRA CHANNEL PROJECT																									
VIBRO CORE SAMPLES										SUMMARY OF LABORATORY TEST RESULTS															
Vibro Core No	Latitude	Longitude	Water depth (m)	Depth (m)	Description	N M.C (%)	Specific Gravity G <sub>s</sub>	w <sub>c</sub> (g/100)	w <sub>e</sub> (g/100)	Void Ratio (e)	Degree of Saturation (S <sub>v</sub> %)	Atterberg Limits			Grain Size Analysis						Torvane (kpa)	Chemical Analysis			
												LL (%)	PL (%)	PI (%)	Shells (%)	Gravel (%)	Coarse Sand (%)	Medium Sand (%)	Fine Sand (%)	Silt & Clay (%)		Ca CO <sub>3</sub> (%)	Organic Matter (%)		
E-E-4	10 0 09.27	79 38 30.06	11.5	0.02	Greyish very soft CLAY	76		1.32	0.78			75	28	45											
				0.75	Greyish very soft CLAY	47		1.28	1.40																
				1.45	Top olive grey loose soft clay with small shells at 1.40m stiff plastic sticky compact olive grey clay. At bottom lighty straw to very light brown compact sandy silty firm clay	29		1.25	1.43						1	2	2	2	33	60	50				
E-E-5	09 59 52.2	79 38 48.30	11.6	0.0	Greyish very soft silty CLAY	54	2.29	1.54	1.0	1.29	85.82	87	29	38							2				
				1.0	Top loose olive grey silty clay with minor plastic clayey pieces and shells. At bottom olive grey firm clay	34		1.79	1.33			87	43	44							25				

Project: SETHU SAMUDRA CHANNEL PROJECT																							
VIBRO CORE SAMPLES										SUMMARY OF LABORATORY TEST RESULTS													
Vibro Core No	Latitude	Longitude	Water depth (m)	Depth (m)	Description	N M.C (%)	Specific Gravity G <sub>s</sub>	γ <sub>w</sub> (g/cc)	γ <sub>s</sub> (g/cc)	Void Ratio (e)	Degree of Saturation (%)	Atterberg Limits			Grain Size Analysis						Torsane (kpa)	Chemical Analysis	
												LL (%)	PL (%)	PI (%)	Shells (%)	Gravel (%)	Coarse Sand (%)	Medium Sand (%)	Fine Sand (%)	Sl. & Clay (%)		Ca CO <sub>3</sub> (%)	Organic Matter (%)
E-E <sub>1</sub> -6	08 59 0.25	79 38 16.08	12.0	0.0	Greyish soft CLAY with fine sand							96	27	69								6.6	1.24
				0.3		59	2.56	1.44	0.91	1.21	21.86										4		
				1.5	Greyish clay with broken shells	30		1.86	1.43			35	19	16									
				3.0	Top olive grey loose soft clay at 20cm semi consolidated olive grey silty clay at 1.50m olive grey clay with lot of broken shells. At bottom light straw coloured to light biscuit colour Compact stiff clay	33	2.33	1.76	1.33	0.75	99.18	94	51	43						60			
E-E <sub>1</sub> -7a	10 08 10.40	79 56 47.00	8.8	0.00	Brownish silty fine to medium SAND	20		1.60	1.58						3	0	0	34	21	42			
				1.20	Top straw yellow to brown medium to fine sand. Bottom near core catcher cement colour medium to fine sand and sand stone pieces	19	2.63	2.0	1.68	0.57	99.38				0	1	0	26	44	29			

Project: SETHU SAMUDRA CHANNEL PROJECT																							
VIBRO CORE SAMPLES										SUMMARY OF LABORATORY TEST RESULTS													
Vibro Core No	Latitude	Longitude	Water depth (m)	Depth (m)	Description	N M.C (%)	Specific Gravity G <sub>s</sub>	γ <sub>w</sub> (g/cc)	γ <sub>s</sub> (g/cc)	Void Ratio (e)	Degree of Saturation (%)	Atterberg Limits			Grain Size Analysis						Torsion (kpa)	Chemical Analysis	
												LL (%)	PL (%)	PI (%)	Shells (%)	Gravel (%)	Coarse Sand (%)	Medium Sand (%)	Fine Sand (%)	Silt & Clay (%)		Ca CO <sub>3</sub> (%)	Organic Matter (%)
E-E <sub>1</sub> -6	08 59 0.25	79 38 16.08	12.0	0.0	Greyish soft CLAY with fine sand	59	2.56	1.44	0.91	1.21	21.86	96	27	69							60	6.6	1.24
				0.3																			
				1.5	Greyish clay with broken shells							35	12	16									
				3.0	Top olive grey loose soft clay at 20cm semi consolidated olive grey silty clay at 1.50m olive grey clay with lot of broken shells. At bottom light straw coloured to light biscuit colour Compact stiff clay							94	51	43									
E-E <sub>1</sub> -7a	10 08 10.40	79 56 47.00	8.8	0.00	Brownish silty fine to medium SAND	20	2.63	2.0	1.68	0.57	88.38				3	0	0	34	21	42			
				1.20	Top straw yellow to brown medium to fine sand. Bottom near core catcher cement colour medium to fine sand and sand stone pieces										0	1	0	26	44	29			



Project: SETHU SAMUDRA CHANNEL PROJECT																							
VIBRO CORE SAMPLES										SUMMARY OF LABORATORY TEST RESULTS													
Vibro Core No	Latitude	Longitude	Water depth (m)	Depth (m)	Description	N M.C. (%)	Specific Gravity G <sub>s</sub>	w (g/cc)	s <sub>c</sub> (g/cc)	Void Ratio (e)	Degree of Saturation (S <sub>r</sub> )	Atterberg Limits			Grain Size Analysis						Texture (figa)	Chemical Analysis	
												LL (%)	PL (%)	PI (%)	Shells (%)	Gravel (%)	Coarse Sand (%)	Medium Sand (%)	Fine Sand (%)	Silt & Clay (%)		Ca CO <sub>3</sub> (%)	Organic Matter (%)
E.E.-10	10°05'04.14	79°55'31.67	8.5	0.0	Brownish medium to fine SAND with shells	4	2.72	1.41	1.35	1.01	10.72				2	0	0	36	57	2			
				1.07	Brownish medium to fine SAND	14		1.78	1.58						1	0	0	17	79	3			
				2.00	Top straw yellow to light brown medium to fine sand. At 2.07 m cement colour medium clayey sand at the bottom of the core barrel light calcareous medium sand with more fine sand and shell pieces and clay.	21		2.02	1.67						1	0	0	9	88	2			
E.E.-11	10°04'08.62	79°49'34.70	10.0	0.00	Olive green very soft CLAY	68		1.86	0.92			51	27	24							2	2.6	12.02
				1.00	Top olive grey soft clay with shell pieces. Between 1.05 and 1.08 olive grey sticky clayey silt, at bottom olive, grey silty sand with shells	29		1.88	1.48						2	0	0	0	55	43			

Project: SETHU SAMUDRA CHANNEL PROJECT																							
VIBRO CORE SAMPLES											SUMMARY OF LABORATORY TEST RESULTS												
Vibro Core No	Latitude	Longitude	Water depth (m)	Depth (m)	Description	N.M.C (%)	Specific Gravity G <sub>s</sub>	γ <sub>s</sub> (g/cc)	γ <sub>m</sub> (g/cc)	Void Ratio (e)	Degree of Saturation (S <sub>v</sub> )	Atterberg Limits			Grain Size Analysis						Tonnage (tpa)	Chemical Analysis	
												LL (%)	PL (%)	PI (%)	Shells (%)	Gravel (%)	Coarse Sand (%)	Medium Sand (%)	Fine Sand (%)	Silt & Clay (%)		Ca CO <sub>3</sub> (%)	Organic Matter (%)
E-E <sub>1</sub> -12	10°05'26.07"	78°55'57.42"	10.0	0.00	Greenish grey clayey silty fine SAND with shells	35										3	0	0	1	96	40		
				0.80	Top grey silty sand. At bottom to the core linear fine olive grey fine silty sand just below end of the core barrel olive grey to fine sand to silty sand	21	2.64	2.05	1.89	0.56	88.62				5	0	0	3	72	25			
E-E <sub>1</sub> -13	10°07'09.60"	78°58'06.69"	8.8	0.0	Greyish soft clayey SILT	33	2.7	1.81	1.36	0.89	60.42	34	NP									2.5	0.17
				1.60	Olive green Calcareous SAND STONE pebbles	14	2.67	1.58	1.39	0.92	40.59												
				1.67	Top grey loose clayey silty to silty clay at 1.67m olive grey medium clayey sand with pieces to calcareous sand stone and shells										0	26	7	25	23	19			

Note: Water depth are measured during operation time

